

黄銅平角棒（熱間） C3604BE-F（相当品）

表1～6

表1

※切断壳可

サイズ(ミリ)			概算Kg
厚み	幅	長さ	
2.0	× 16	× 2000	0.6
2.0	× 18	× 2000	0.7
2.0	× 20	× 2000	0.7
2.0	× 25	× 2000	0.9
2.5	× 9	× 2000	0.4
2.5	× 12	× 2000	0.6
3.0	× 4.5	× 2000	0.3
3.0	× 6	× 4000	0.7
3.0	× 8	× 4000	0.9
3.0	× 9	× 4000	1.0
3.0	× 10	× 4000	1.1
3.0	× 12	× 4000	1.3
3.0	× 15	× 4000	1.6
3.0	× 16	× 4000	1.7
3.0	× 18	× 4000	1.9
3.0	× 19	× 4000	2.0
3.0	× 20	× 4000	2.1
3.0	× 22	× 4000	2.3
3.0	× 25	× 4000	2.6
3.0	× 30	× 4000	3.1
3.0	× 32	× 4000	3.3
3.0	× 35	× 4000	3.6
3.0	× 38	× 4000	3.9
3.0	× 40	× 4000	4.1
3.0	× 45	× 4000	4.6
3.0	× 50	× 4000	5.1
4.0	× 6	× 4000	0.9
4.0	× 7	× 4000	1.0
4.0	× 8	× 4000	1.1
4.0	× 9	× 4000	1.3
4.0	× 10	× 4000	1.4
4.0	× 12	× 4000	1.7
4.0	× 15	× 4000	2.1
4.0	× 16	× 4000	2.2
4.0	× 18	× 4000	2.5
4.0	× 20	× 4000	2.8
4.0	× 25	× 4000	3.4

表2

※切断壳可

サイズ(ミリ)			概算Kg
厚み	幅	長さ	
4.0	× 30	× 4000	4.1
4.0	× 32	× 4000	4.4
4.0	× 35	× 4000	4.8
4.0	× 40	× 4000	5.5
4.0	× 50	× 4000	6.8
4.5	× 6	× 4000	1.0
4.5	× 9	× 4000	1.4
4.5	× 10	× 4000	1.6
4.5	× 12	× 4000	1.9
4.5	× 15	× 4000	2.3
4.5	× 18	× 4000	2.8
4.5	× 20	× 4000	3.1
4.5	× 25	× 4000	3.9
4.5	× 30	× 4000	4.6
4.5	× 35	× 4000	5.4
4.5	× 38	× 4000	5.9
4.5	× 50	× 4000	7.7
5.0	× 10	× 4000	1.7
5.0	× 12	× 4000	2.1
5.0	× 15	× 4000	2.6
5.0	× 16	× 4000	2.8
5.0	× 19	× 4000	3.3
5.0	× 20	× 4000	3.4
5.0	× 25	× 4000	4.3
5.0	× 30	× 4000	5.1
5.0	× 32	× 4000	5.5
5.0	× 35	× 4000	6.0
5.0	× 40	× 4000	6.8
5.0	× 45	× 4000	7.7
5.0	× 50	× 4000	8.5
5.0	× 60	× 4000	10.2
6.0	× 8	× 4000	1.7
6.0	× 9	× 4000	1.9
6.0	× 10	× 4000	2.1
6.0	× 12	× 4000	2.5
6.0	× 13	× 4000	2.7
6.0	× 14	× 4000	2.9

黄銅平角棒（熱間） C3604BE-F（相当品）

表1~6

表3

※切断壳可

サイズ(ミリ)			
厚み	幅	長さ	概算Kg
6.0	× 15	× 4000	3.1
6.0	× 16	× 4000	3.3
6.0	× 18	× 4000	3.7
6.0	× 19	× 4000	3.9
6.0	× 20	× 4000	4.1
6.0	× 21	× 4000	4.3
6.0	× 22	× 4000	4.5
6.0	× 25	× 4000	5.1
6.0	× 30	× 4000	6.2
6.0	× 32	× 4000	6.6
6.0	× 35	× 4000	7.2
6.0	× 38	× 4000	7.8
6.0	× 40	× 4000	8.2
6.0	× 45	× 4000	9.2
6.0	× 50	× 4000	10.2
6.0	× 60	× 4000	12.3
6.0	× 65	× 4000	13.3
6.0	× 75	× 4000	15.3
6.0	× 100	× 4000	20.4
7.0	× 12	× 4000	2.9
7.0	× 13	× 4000	3.1
7.0	× 20	× 4000	4.8
7.0	× 50	× 4000	11.9
8.0	× 10	× 4000	2.8
8.0	× 12	× 4000	3.3
8.0	× 14	× 4000	3.9
8.0	× 15	× 4000	4.1
8.0	× 16	× 4000	4.4
8.0	× 18	× 4000	4.9
8.0	× 20	× 4000	5.5
8.0	× 22	× 4000	6.0
8.0	× 25	× 4000	6.8
8.0	× 30	× 4000	8.2
8.0	× 35	× 4000	9.6
8.0	× 38	× 4000	10.4
8.0	× 40	× 4000	10.9
8.0	× 50	× 4000	13.6

表4

※切断壳可

サイズ(ミリ)			
厚み	幅	長さ	概算Kg
8.0	× 60	× 4000	16.4
8.0	× 75	× 4000	20.4
8.0	× 100	× 4000	27.2
9.0	× 12	× 4000	3.7
9.0	× 15	× 4000	4.6
9.0	× 18	× 4000	5.6
9.0	× 20	× 4000	6.2
9.0	× 25	× 4000	7.7
9.0	× 30	× 4000	9.2
9.0	× 32	× 4000	9.8
9.0	× 35	× 4000	10.8
9.0	× 38	× 4000	11.7
9.0	× 40	× 4000	12.3
9.0	× 50	× 4000	15.3
10.0	× 12	× 4000	4.1
10.0	× 15	× 4000	5.1
10.0	× 16	× 4000	5.5
10.0	× 18	× 4000	6.2
10.0	× 20	× 4000	6.8
10.0	× 22	× 4000	7.5
10.0	× 25	× 4000	8.5
10.0	× 30	× 4000	10.2
10.0	× 35	× 4000	11.9
10.0	× 40	× 4000	13.6
10.0	× 45	× 4000	15.3
10.0	× 50	× 4000	17.0
10.0	× 55	× 4000	18.7
10.0	× 60	× 4000	20.4
10.0	× 65	× 4000	22.1
10.0	× 75	× 4000	25.5
10.0	× 80	× 4000	27.2
10.0	× 100	× 4000	34.0
12.0	× 14	× 4000	5.8
12.0	× 15	× 4000	6.2
12.0	× 16	× 4000	6.6
12.0	× 18	× 4000	7.4
12.0	× 20	× 4000	8.2

黄銅平角棒（熱間） C3604BE-F（相当品）

表1~6

表5

※切断壳可

サイズ(ミリ)			
厚み	幅	長さ	概算Kg
12.0	× 22	× 4000	9.0
12.0	× 25	× 4000	10.2
12.0	× 30	× 4000	12.3
12.0	× 32	× 4000	13.1
12.0	× 35	× 4000	14.3
12.0	× 38	× 4000	15.5
12.0	× 40	× 4000	16.4
12.0	× 45	× 4000	18.4
12.0	× 50	× 4000	20.4
12.0	× 55	× 4000	22.5
12.0	× 60	× 4000	24.5
12.0	× 80	× 4000	32.7
12.0	× 100	× 4000	40.8
13.0	× 25	× 4000	11.1
14.0	× 20	× 4000	9.6
15.0	× 20	× 4000	10.2
15.0	× 22	× 4000	11.3
15.0	× 25	× 4000	12.8
15.0	× 30	× 4000	15.3
15.0	× 35	× 4000	17.9
15.0	× 40	× 4000	20.4
15.0	× 45	× 4000	23.0
15.0	× 50	× 4000	25.5
15.0	× 55	× 4000	28.1
15.0	× 60	× 4000	30.6
15.0	× 65	× 4000	33.2
15.0	× 80	× 4000	40.8
15.0	× 100	× 4000	51.0
16.0	× 18	× 4000	9.8
16.0	× 20	× 4000	10.9
16.0	× 25	× 4000	13.6
16.0	× 30	× 4000	16.4
16.0	× 35	× 4000	19.1
16.0	× 40	× 4000	21.8
16.0	× 45	× 4000	24.5

表6

※切断壳可

サイズ(ミリ)			
厚み	幅	長さ	概算Kg
16.0	× 50	× 4000	27.2
17.0	× 25	× 4000	14.5
18.0	× 20	× 4000	12.3
20.0	× 25	× 4000	17.0
20.0	× 30	× 4000	20.4
20.0	× 35	× 4000	23.8
20.0	× 40	× 4000	27.2
20.0	× 45	× 4000	30.6
20.0	× 50	× 4000	34.0
20.0	× 55	× 4000	37.4
20.0	× 60	× 4000	40.8
20.0	× 65	× 4000	44.2
20.0	× 75	× 4000	51.0
20.0	× 100	× 4000	68.0
22.0	× 40	× 4000	30.0
25.0	× 30	× 4000	25.5
25.0	× 35	× 4000	29.8
25.0	× 40	× 4000	34.0
25.0	× 45	× 4000	38.3
25.0	× 50	× 4000	42.5
25.0	× 55	× 4000	46.8
25.0	× 60	× 4000	51.0
25.0	× 75	× 4000	63.8
30.0	× 35	× 4000	35.7
30.0	× 40	× 4000	40.8
30.0	× 45	× 4000	45.9
30.0	× 50	× 4000	51.0
30.0	× 55	× 4000	56.1
30.0	× 60	× 4000	61.2
30.0	× 65	× 4000	66.3
30.0	× 75	× 4000	76.5
35.0	× 40	× 4000	47.6
35.0	× 50	× 4000	59.5
35.0	× 60	× 4000	71.4
40.0	× 80	× 2000	54.4

黄銅平角棒（冷間） C3604BD-F (JIS H 3250)

表1~3

表1

※切断壳不可

サイズ (ミリ)				概算 Kg
厚み	幅	長さ		
2.0	× 5	×	2000	0.2
2.0	× 6	×	2000	0.2
2.0	× 8	×	2000	0.3
2.0	× 9	×	2000	0.4
2.0	× 10	×	2000	0.4
2.0	× 12	×	2000	0.5
2.0	× 15	×	2000	0.6
2.0	× 18	×	2000	0.7
2.0	× 20	×	2000	0.7
2.0	× 25	×	2000	0.9
2.0	× 30	×	2000	1.1
3.0	× 6	×	2000	0.4
3.0	× 8	×	2000	0.5
3.0	× 9	×	2000	0.5
3.0	× 10	×	2000	0.6
3.0	× 12	×	2000	0.7
3.0	× 14	×	2000	0.8
3.0	× 15	×	2000	0.8
3.0	× 16	×	2000	0.9
3.0	× 18	×	2000	1.0
3.0	× 20	×	2000	1.1
3.0	× 25	×	2000	1.3
3.0	× 30	×	2000	1.6
3.0	× 33	×	2000	1.7
3.0	× 35	×	2000	1.8
3.0	× 40	×	2000	2.1
3.0	× 45	×	2000	2.3
3.0	× 50	×	2000	2.6
4.0	× 5	×	2000	0.4
4.0	× 6	×	2000	0.5
4.0	× 8	×	2000	0.6
4.0	× 9	×	2000	0.7
4.0	× 10	×	2000	0.7
4.0	× 12	×	2000	0.9
4.0	× 15	×	2000	1.1
4.0	× 16	×	2000	1.1
4.0	× 20	×	2000	1.4

表2

※切断壳不可

サイズ (ミリ)				概算 Kg
厚み	幅	長さ		
4.0	× 25	×	2000	1.7
4.0	× 30	×	2000	2.1
4.0	× 33	×	2000	2.3
4.0	× 35	×	2000	2.4
4.0	× 40	×	2000	2.8
4.0	× 45	×	2000	3.1
4.0	× 50	×	2000	3.4
5.0	× 10	×	2000	0.9
5.0	× 12	×	2000	1.1
5.0	× 15	×	2000	1.3
5.0	× 16	×	2000	1.4
5.0	× 20	×	2000	1.7
5.0	× 25	×	2000	2.2
5.0	× 30	×	2000	2.6
5.0	× 35	×	2000	3.0
5.0	× 40	×	2000	3.4
5.0	× 45	×	2000	3.9
5.0	× 50	×	2000	4.3
6.0	× 8	×	2000	0.9
6.0	× 9	×	2000	1.0
6.0	× 10	×	2000	1.1
6.0	× 12	×	2000	1.3
6.0	× 15	×	2000	1.6
6.0	× 16	×	2000	1.7
6.0	× 20	×	2000	2.1
6.0	× 30	×	2000	3.1
6.0	× 40	×	2000	4.1
6.0	× 45	×	2000	4.6
6.0	× 50	×	2000	5.1
8.0	× 10	×	2000	1.4
8.0	× 12	×	2000	1.7
8.0	× 14	×	2000	1.9
8.0	× 15	×	2000	2.1
8.0	× 20	×	2000	2.8
8.0	× 30	×	2000	4.1
8.0	× 40	×	2000	5.5
8.0	× 45	×	2000	6.2

黄銅平角棒（冷間） 表1~3
C3604BD-F (JIS H 3250)

表3

※切断壳不可

サイズ(ミリ)			概算Kg
厚み	幅	長さ	
8.0	× 50	× 2000	6.8
10.0	× 12	× 2000	2.1
10.0	× 15	× 2000	2.6
10.0	× 20	× 2000	3.4
10.0	× 25	× 2000	4.3
10.0	× 30	× 2000	5.1
10.0	× 35	× 2000	6.0
10.0	× 40	× 2000	6.8
10.0	× 50	× 2000	8.5
12.0	× 15	× 2000	3.1
12.0	× 20	× 2000	4.1
12.0	× 25	× 2000	5.1
12.0	× 26	× 2000	5.3
12.0	× 30	× 2000	6.2
12.0	× 35	× 2000	7.2
12.0	× 40	× 2000	8.2
14.0	× 16	× 2000	3.9
15.0	× 20	× 2000	5.1
15.0	× 25	× 2000	6.4
15.0	× 30	× 2000	7.7
15.0	× 35	× 2000	9.0
15.0	× 40	× 2000	10.2
15.0	× 50	× 2000	12.8
18.0	× 20	× 2000	6.2
20.0	× 25	× 2000	8.5
20.0	× 30	× 2000	10.2
20.0	× 35	× 2000	11.9
20.0	× 40	× 2000	13.6
20.0	× 50	× 2000	17.0
25.0	× 30	× 2000	12.8
25.0	× 35	× 2000	14.9
25.0	× 40	× 2000	17.0

カドミレス黄銅平角棒（冷間）
C3604BD-F (JIS H 3250)

表1

※切断壳不可

サイズ(ミリ)			概算Kg
厚み	幅	長さ	
2.0	× 10	× 2500	0.5
3.0	× 9	× 2500	0.6
3.0	× 10	× 2500	0.7
3.0	× 12	× 2500	0.8
3.0	× 15	× 2500	1.0
3.0	× 20	× 2500	1.3
3.0	× 25	× 2500	1.6
3.0	× 30	× 2500	2.0
4.0	× 10	× 2500	0.9
4.0	× 12	× 2500	1.1
4.0	× 15	× 2500	1.3
5.0	× 12	× 2500	1.3
5.0	× 15	× 2500	1.6
5.0	× 20	× 2500	2.2
5.0	× 25	× 2500	2.7
5.0	× 30	× 2500	3.2
5.0	× 40	× 2500	4.3
5.0	× 50	× 2500	5.4
6.0	× 20	× 2500	2.6
6.0	× 25	× 2500	3.2
6.0	× 30	× 2500	3.9
6.0	× 40	× 2500	5.1
6.0	× 45	× 2500	5.8
6.0	× 50	× 2500	6.4

カドミレス黄銅平角棒（熱間） C3604BE-F (JIS H 3250) 表1~2

表1

※切断壳不可

サイズ (ミリ)			概算 Kg
厚み	幅	長さ	
8.0	10	4000	2.8
8.0	12	4000	3.3
8.0	18	4000	4.9
8.0	20	4000	5.5
8.0	30	4000	8.2
8.0	35	4000	9.6
8.0	40	4000	10.9
10.0	12	4000	4.1
10.0	15	4000	5.1
10.0	20	4000	6.8
10.0	25	4000	8.5
10.0	30	4000	10.2
10.0	35	4000	11.9
10.0	40	4000	13.6
10.0	45	4000	15.3
10.0	50	4000	17.0
12.0	18	4000	7.4
12.0	20	4000	8.2
12.0	25	4000	10.2
12.0	30	4000	12.3
12.0	35	4000	14.3
12.0	40	4000	16.4
12.0	50	4000	20.4
15.0	20	4000	10.2
15.0	25	4000	12.8

表2

※切断壳不可

サイズ (ミリ)			概算 Kg
厚み	幅	長さ	
15.0	30	4000	15.3
15.0	35	4000	17.9
15.0	40	4000	20.4
15.0	45	4000	23.0
15.0	50	4000	25.5
20.0	25	4000	17.0
20.0	30	4000	20.4
20.0	35	4000	23.8
20.0	40	4000	27.2
20.0	45	4000	30.6
20.0	50	4000	34.0
25.0	30	4000	25.5
25.0	35	4000	29.8
25.0	40	4000	34.0
25.0	45	4000	38.3
25.0	50	4000	42.5
25.0	60	4000	51.0
30.0	35	4000	35.7
30.0	40	4000	40.8
30.0	45	4000	45.9
30.0	50	4000	51.0
30.0	55	4000	56.1
30.0	60	4000	61.2
35.0	50	4000	59.5
40.0	80	2000	54.4